

Dalapro Plus Hydro

Product information

Dalapro Plus Hydro is a blue-toned polymer adhesive specially adapted for wet areas. The blue colour is permanent and added for easy identifying of the product. Dalapro Plus Hydro can be used on common substrates such as plasterboards, wooden panels, plaster and painted surfaces for lining fibreglass, cellulose/polyester or vinyl-wall covering.

The product fulfils the Swedish wallpaper industries trade organisation requirements for adhesives and is manufactured in accordance with ISO 9001 and ISO 14001.

Instructions

Apply Dalapro Plus Hydro using a roller, paintbrush or an airless sprayer at a minimum temperature of +5°C. Surfaces should be clean, dry and firmly attached and previously painted surfaces must be washed and sanded. Follow your local branch regulations and recommendations.

Consumption of material

Ca 0.2 liter/m²

Storage

Protect from frost and direct sunlight. The packaging is marked with best-before date. Unopened packs can be stored in 12 months.

TECHNICAL DATA

Binder

Latex co-polymer

Solvent

Water

Filler

Approx. 1.0 kg/l

pH

Approx. 9

Colour

Blue

Flammability

Does not spread or support fire

Cleaning

Use water for tools and spillage

Packaging

5-and 15 l plastic bucket

Range of application

For indoor use

The information contained in this data sheet is the result of our study and experience. It is offered in good faith and cannot a guarantee and no liability is assumed. We reserve the right to change any product information included in this document without prior information.

For latest product information: www.dalapro.com

Last updated 2010-06-15

