

Dalapro Airless S

PRODUCT INFORMATION

Dalapro Airless S is an all-round classical white spray filler. Dalapro Airless S can be used for smoothing and spray-texturing on common types of walls and ceilings. Fine dolomite marble provides maximum whiteness and build. The product is manufactured in accordance with ISO 9001 and ISO 14001.

Instructions

Apply using a filler sprayer on clean, dry and firmly attached surfaces at a minimum temperature of +5° C. Use sandpaper, particle size 100-120, when sanding the dry surface. Eye protection and dust mask are recommended when sanding. Filled surfaces should be primed before wallpapering. Follow your local branch regulations and recommendations.

Consumption of material

Thin coat plastering = 1 litre/ m² per mm

Spray-texturing = approx. 0.3 litre/m²

Drying time

The drying time is dependent on substrate, layer thickness, temperature, ventilation and atmospheric conditions.

Storage

Protect from frost and direct sunlight. The packaging is marked with best-before date. Unopened packs can be stored in 12 months.



TECHNICAL DATA

Binder:	Latex co-polymer
Solvent:	Water
Filler:	White dolomite
Particle size:	Max 0,3 mm
Bulk density:	Approx. 1,8 kg/l
Vol. non-volatile matter:	Approx. 56%
pH:	Approx. 9
Colour:	White
Build:	High
Flammability:	Does not spread or support fire
Cleaning:	Use water for tools and spillage
Packaging:	15 l plastic bucket, 15 plastic bag
Range of application:	For indoor use

The information contained in this data sheet is the result of our study and experience. It is offered in good faith and cannot a guarantee and no liability is assumed. We reserve the right to change any product information included in this document without prior information.

For latest product information:
www.dalapro.com

Last updated 2011-01-18

Dalapro

phone: +46 19 46 34 00 • fax: +46 19 46 57 31 • info@dalapro.se • www.dalapro.com