

# Dalapro Premium DM60

## Product information

Dalapro Premium DM60 is a white multifunctional powder product specially made for repairs on common substrates. Dalapro Premium DM60 is easy to mix and provides no shrinkage. For larger projects use Dalapro Premium ready mix.

The product fulfils the CE requirements according to EN 13963 and EN 13279-1.

## Instructions

Apply at a minimum temperature of +5° C. Massive or non-absorbing surfaces should be dry, cleaned and primed. Try a minor surface in order to confirm good adhesiveness to the substrate. Eye protection and dust mask are recommended when sanding the dry surface. Use sandpaper, particle size 100-120. Filled surfaces should be primed before wallpapering or painting.

## Storage

Unopened packs can be stored for 12 months from production date in a dry place.

Opened bags should be shut and consumed within three months.

The information contained in this data sheet is the result of our study and experience. It is offered in good faith and cannot a guarantee and no liability is assumed. We reserve the right to change any product information included in this document without prior information.

For latest product information: [www.dalapro.com](http://www.dalapro.com)

Last updated 2010-05-24

## TECHNICAL DATA

### Binder

Polymer-reinforced plaster

### Mixture

1 part water - 2 parts powder  
Pour the powder into the water and let "draw" for 3-5 minutes before stirring

### Open time

Max. 60 min.

### Colour

White

### Build

High. Minimum shrinkage

### Consumption of material

Approx. 0.9 kg/m<sup>2</sup>/mm

### Flammability

Does not spread or support fire

### Cleaning

Use water for tools and spillage

### Packaging

Paper bag 12.5 kg

### Range of application

For indoor use

