

Strikolith Universal Primer

Product Name:

Strikolith Universal Primer

Composition:

A high quality, factory-prepared primer based on a high-grade dispersion binder. Additives for improving the stabilising properties and quartz-containing fillers.

Properties:

Strikolith Universal Primer is a quartz-containing, pigmented primer with stabilising properties. Strikolith Universal Primer is suitable for interior and exterior application. Strikolith Universal Primer is an essential basic component in the set-up of a durable synthetic resin-bound plaster system. Strikolith Universal Primer forms an excellent bonding bridge, is permanently elastic, permeable to moisture, weather-resistant and rainproof.

Colors:

Natural or as per the Strikolith colour palette.

Use:

Strikolith Universal Primer is for application on mineral surfaces, as a bonding bridge for Strikolith adhesive, hand and machine gypsum, and synthetic resin-bound Decorative and Spachtelpleister plasters. For a synthetic resin-bound finish, always apply Strikolith Universal Primer in the colour of the chosen finish.

Technical data:

- S.G.: approx. 1.5 g / cm³.
- PH-value: approx. 7 - 9.
- Viscosity: 10,000 mPa.s.

Surface preparation:

Thoroughly remove old, dusty and dirty loose plaster and layers of paint. Remove grease deposits and other contaminations with Strikolith Streakoclean.

For interior application: first treat strongly absorbing surfaces and gypsum surfaces (e.g. plaster blocks) with one layer of Strikolith Deep Primer. Pretreat powdery and sandy surfaces with two layers of Strikolith Deep Primer, applying wet on wet. For exterior application: depending on the nature and quality of the surface, carry out repairs with a suitable Strikocem mineral plaster. Observe sufficient drying time if lime-containing products have either been applied for repairs or used when fully plastering over the surface.

When applying a further synthetic resin-bound finish, pretreat the whole with one layer of Strikolith Deep Primer after it has fully dried.

Strikolith Universal Primer as a bonding bridge for a further layer of gypsum plaster reduces and evens out (strong) absorption from the surface, and also provides an increase in the surface area/adhesion.

In the case of too strong an absorption, variations in absorption, and/or powdery surfaces, it is recommended to apply Strikolith Deep Primer beforehand.

General Processing:

Apply Strikolith Universal Primer thinned, with a block brush or roller. Thin the Primer with max. 5% tap water. When applying decorative plasters, always apply the Primer in the colour of the top coat. Drying time at least 24 hours. Immediately clean brushes and tools with water after use.

Consumption:

Approx. 350 grams per m², depending on the surface.

Packaging:

8 en 22 kg in kunststof emmer.

Storage:

Can be kept in a cool and frost-free place for about 1 year.

Strikolith Universal Primer

Safety:

It is recommended to properly protect the eyes, nose, mouth and skin using personal protective equipment while applying primers. If Strikolith Universal Primer comes into contact with the eyes, immediately rinse with copious amounts of clean water (for about 15 mins). Afterwards consult a doctor. For more information, consult the Strikolith safety sheet.

Particularities:

Building components that are not being treated with Strikolith Universal Primer must be protected beforehand using paper and masking tape. Remove immediately after applying the Primer. Do not apply below a substrate and air temperature of +5°C or if frost is expected.